

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
12 September 2003 (12.09.2003)

PCT

(10) International Publication Number
WO 03/075056 A1

(51) International Patent Classification⁷: **G02B 6/12**

(21) International Application Number: PCT/EP02/02484

(22) International Filing Date: 6 March 2002 (06.03.2002)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **PIRELLI S.P.A.** [IT/IT]; Viale Sarca, 222, I-20126 Milano (IT).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ROMAGNOLI, Marco** [IT/IT]; Via della Moscova, 66, I-20121 Milano (IT). **TORMEN, Maurizio** [IT/IT]; Via Agordo, 13, I-32100 Belluno (IT). **BONATI, Camilla** [IT/IT]; Via S. Sofia, 21, I-20122 Milano (IT).

(74) Agents: **BATTIPEDE, Francesco** et al.; Pirelli S.p.A., Viale Sarca, 222, I-20126 Milano (IT).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **DEVICE FOR CROSSING OPTICAL BEAMS, IN PARTICULAR IN AN INTEGRATED OPTICAL CIRCUIT**



(57) Abstract: A device (400) for crossing optical beams comprises at least first input optical waveguide (402') directed along a first axis, a second optical waveguide (403') directed along a second axis inclined with respect to the first axis, and a photonic crystal (401) having a regular periodicity in an optical crossing region at the intersection of said first and second axis comprises; opposite the first and second input waveguides (402', 403'), a first and a second output waveguides (402'', 403'') are provided for the exit beams.